



MICROLUX®

Catalogue number

MCLT66/26W/3MD/840

CE 230V 50Hz

To specify:

Catalogue number: MCLT66/26W/3MD/840. Luxonic MICROLUX®

A 26 Watt modular recessed, 3180 lumen output colour 840 LED luminaire, achieving 122 luminaire exit lumens per circuit Watt, designed to suit 15 & 24 mm exposed T-bar ceilings. An acrylic Tp(b) micro-structure lens controls light distribution and luminance, suppressing high-angle light above 65 deg. to meet the UGR and luminance limits recommended by BS-EN 12464, CIBSE LG7 and the BCO.

Constructed from a robust polyester powder-coated steel housing, sealed to IP44 to front face with RAL 9010, 20% gloss finish.

Complete with 3 hour DALI maintained remote emergency facility.

Size 595 x 595 x 80 mm

| | |
|------------------------------------|-------------------------------|
| Mounting: | Recessed in ceiling |
| Total Lamp Lumens: | 3180 |
| CRI (Ra): | 80 |
| Lamp Colour (K): | 4000 |
| Size LxWxH (mm): | 595 x 595 x 80 |
| Total Circuit Watts: | 26 |
| Luminaire Lumens Per Circuit Watt: | 122 |
| IP Rating: | IP44 |
| Emergency: | DALI maintained 3 hour remote |

