



MICROLUX®

Catalogue number

MCLT66/26W/DIM8/3MET/840

CE 230V 50Hz

To specify:

Catalogue number: MCLT66/26W/DIM8/3MET/840. Luxonic MICROLUX®

A 26 Watt modular recessed, 3180 lumen output colour 840 LED luminaire, achieving 122 luminaire exit lumens per circuit Watt, designed to suit 15 & 24 mm exposed T-bar ceilings. The acrylic micro-structure Tp(b) lens controls light distribution and luminance, suppressing high-angle light above 65 deg. to meet the UGR less than 19 and luminance limits recommended by BS-EN 12464, CIBSE LG7 and the BCO.

Constructed from a robust polyester powder-coated steel housing, sealed to IP44 to front face with RAL 9010, 20% gloss finish.

Complete with DALI control gear and 3 hour self-test maintained remote emergency facility.

Size 595 x 595 x 80 mm depth

Mounting:	Recessed in ceiling
Total Lamp Lumens:	3180
CRI (Ra):	80
Lamp Colour (K):	4000
Size LxWxH (mm):	595 x 595 x 80
Total Circuit Watts:	26
Luminaire Lumens Per Circuit Watt:	122
IP Rating:	IP44
Emergency:	Self-test maintained 3 hour remote

