



## MICROLUX®

### Catalogue number

**MCLT66/26W/3MD/840**

**CE 230V 50Hz**

### To specify:

Catalogue number: MCLT66/26W/3MD/840. Luxonic MICROLUX®

A 26 Watt modular recessed, 3180 lumen output colour 840 LED luminaire, achieving 122 luminaire exit lumens per circuit Watt, designed to suit 15 & 24 mm exposed T-bar ceilings. An acrylic Tp(b) micro-structure lens controls light distribution and luminance, suppressing high-angle light above 65 deg. to meet the UGR and luminance limits recommended by BS-EN 12464, CIBSE LG7 and the BCO.

Constructed from a robust polyester powder-coated steel housing, sealed to IP44 to front face with RAL 9010, 20% gloss finish.

Complete with 3 hour DALI maintained remote emergency facility.

Size 595 x 595 x 80 mm

|                                    |                               |
|------------------------------------|-------------------------------|
| Mounting:                          | Recessed in ceiling           |
| Total Lamp Lumens:                 | 3180                          |
| CRI (Ra):                          | 80                            |
| Lamp Colour (K):                   | 4000                          |
| Size LxWxH (mm):                   | 595 x 595 x 80                |
| Total Circuit Watts:               | 26                            |
| Luminaire Lumens Per Circuit Watt: | 122                           |
| IP Rating:                         | IP44                          |
| Emergency:                         | DALI maintained 3 hour remote |

