



## MICROLUX®

### Catalogue number

**MCLT66/31W/840**

**CE 230V 50Hz**

### To specify:

Catalogue number: MCLT66/31W/840. Luxonic MICROLUX®

A 31 Watt modular recessed, 3600 lumen output colour 840 LED luminaire, achieving 116 luminaire exit lumens per circuit Watt, designed to suit 15 & 24 mm exposed T-bar ceilings. The acrylic micro-structure Tp(b) lens controls light distribution and luminance, suppressing high-angle light above 65 deg. to meet the UGR less than 19 and luminance limits recommended by BS-EN 12464, CIBSE LG7 and the BCO.

Constructed from a robust polyester powder-coated steel housing, sealed to IP44 to front face with RAL 9010, 20% gloss finish.

Size 595 x 595 x 80 mm depth

|                                    |                     |
|------------------------------------|---------------------|
| Mounting:                          | Recessed in ceiling |
| Total Lamp Lumens:                 | 3600                |
| CRI (Ra):                          | 80                  |
| Lamp Colour (K):                   | 4000                |
| Size LxWxH (mm):                   | 595 x 595 x 80      |
| Total Circuit Watts:               | 31                  |
| Luminaire Lumens Per Circuit Watt: | 116                 |
| IP Rating:                         | IP44                |

